

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025215 A1

(51) International Patent Classification⁷: G01B 7/012, 3/00

(21) International Application Number:
PCT/GB2003/003863

(22) International Filing Date:
5 September 2003 (05.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0221255.3 13 September 2002 (13.09.2002) GB

(71) Applicant (for all designated States except US): REN-
ISHAW PLC [GB/GB]; New Mills, Wotton-under-Edge,
Gloucestershire GL12 8JR (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LUMMES,

Stephen, Edward [GB/GB]; Alma Place, Beech Knapp,
Burleigh, Stroud, Gloucestershire GL5 2PS (GB). Mc-
MURTRY, David, Roberts [GB/GB]; Park Farm,
Stancombe, Dursley,, Gloucestershire GL11 6AT (GB).


(74) Agent: FOWLER, Maria, Jayne; Renishaw plc, Patent
Department, New Mills, Wotton-under-Edge, Gloucester-
shire GL12 8JR (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: TOUCH PROBE



(57) **Abstract:** A touch probe (10,50) is disclosed comprising a probe body (12,52) housing first locating elements (23,58), a stylus holder (16,54) having second locating elements (24,57) which co-operate with the first locating elements to locate the stylus holder within the probe body, and a bias (36,68,86) to urge the first and second locating elements into contact, wherein an element (35,50,76,90) is provided to damp motion between the probe body and the stylus holder. The element may slow a relative movement between the locating elements perhaps by resisting the urging of the bias or absorb energy produced by a relative movement between the probe body and stylus holder. The element may be slidably or rotatably mounted with respect to one of the probe head and stylus holder.

WO 2004/025215 A1